



ROPPE.
Proven. Flooring. Experiences.


RENEW SVT
SOLID VINYL TILE

RENEW SVT


SOLID VINYL TILE




ReNew Solid Vinyl Tile is durable, versatile and easy to maintain, and comes with the natural slip resistance of cork. ReNew Solid Vinyl Tile is great for installations that require minimal maintenance requirements as it easily buffs to a shine with no finishes required! It's also colorful, stylish and available in some coordinating white marble designs. The 24" x 24" and 36" x 36" tiles are available pre-grooved for heat weldable installations.



Z188
brick



Z639
beigewood



Z663
aged fern



Z193
black brown



Z100
black



Zw100
white black

VINYL WELDING BEADS


Ensure proper fit, finish and appearance by using vinyl welding bead in areas that require ongoing and comprehensive wet cleaning and where maintaining proper hygiene is essential. Vinyl Welding Beads are available in 200l/f spools.

VINYL WELDING BEADS COLORS

- 100 black
- 193 black brown
- 150 dark gray
- 194 burnt umber
- 197 iceberg
- 627 mariner
- 191 camel
- 137 cinnabar
- 188 brick
- 639 beigewood
- 663 aged fern
- 621 merlin

ROPPE


Proven. Flooring. Experiences.




Z197
iceberg




Zw197
white iceberg



Z194
burnt umber



Z137
cinnabar




Z150
dark gray




Z191
camel



Zw191
white camel



Z621
merlin



Z627
mariner



Zw627
white mariner



Cork is bark tissue harvested from *Quercus suber* oaks, a tree native to Southwest Europe and Northwest Africa. Cork is impermeable, which aids in increased slip resistance, and also features fire retardant and elastic properties. It takes 25 years for a cork oak trunk to mature. Half of all cork trees are located in Portugal, and Portuguese law prohibits stripping the trees more than once every nine years in order to protect the species.

RENEW SVT

SOLID VINYL TILE




Bio-Based and Phthalate Free

Formulated using bio-based phthalate-free plasticizer, from a rapidly renewable resource.



Sustainable Solutions

Made in the U.S.A. and meets GREENGUARD Gold and CHPS criteria.




Aesthetic Appeal

Cork content provides aesthetic appeal and may improve slip resistance when moisture is present, when tested in wet conditions using ASTM D2047.



Flexible, Yet Strong

Flexible enough to self-cove during installation, but can withstand extreme static rolling loads up to 2,000 psi.



Variety of Sizes, Heat Weldable

Available in .080" thick 12" x 12" and pre-grooved, heat weld 24" x 24" or 36" x 36" tiles for seamless installation with matching vinyl welding beads.



Single Price Point

All colors available at a Single Price Point. Available in 16 colors. Color is inherent throughout the tile thickness.



Installation



Roppe products are easy to install & maintain using our Excelsior™ Products. Visit roppe.com for the most current recommendations.



Maintenance

Find the most current lineup of Roppe product folders online at roppe.com.



Digital Folders

ROPPE
Proven. Flooring. Experiences.




Sustainable
Minds®

ROPPE 
UNIVERSITY



Health
Product
Declaration®
is available at
roppe.com

proudly made in the


78-671 10/23