

PRODUCT DESCRIPTION

PR-930 is a finish remover specifically designed to remove topically applied flooring finishes over resilient flooring products that are sensitive to alkalinity, such as rubber flooring and crumb/recycled rubber flooring. PR-930 allows for the removal of these finishes without causing damage to pH sensitive flooring

products. PR-930 is designed to remove multiple layers of floor finish, even if heavily soiled or thickly applied.

FEATURES

- **Low Alkalinity**
- **Normal Stripping or Heavy Removal**
- **Reduces Application & Removal Times**
- **Compatible with pH Sensitive Flooring**
- **Prevents Discoloration of Sensitive Flooring**
- **Compatible With Most Resilient Flooring Products**

TECHNICAL INFORMATION

Unit Size: **1 Gallon**
 Weight: **8.07 lbs.**
 VOC: **9%**
 pH: **8-9**
 Flash Point: **176° F**
 Surface Cleaning Dilution: **4 oz. per Gallon**
 Normal Stripping Dilution: **32 oz. per Gallon**
 Heavy-Duty Removal Dilution: **64 oz. per Gallon**
 Diluted Gallons Per Unit: **3 - 5 Gallons**
 Coverage Per Diluted Gallon: **75 - 100 sq. ft.**
 Coverage Per Unit: **150 - 500 sq. ft.**
 Shelf Life: **1 Year**
 Storage Temperature: **50° - 75° F**

1. COLOR STABILITY

Prior to use, ensure that the flooring material is color-stable when treated with the FR-920, as manufacturer is not responsible for color changes within flooring products where the FR-920 is used.

2. APPLICATION INSTRUCTIONS

Prior to cleaning, sweep, dust mop and/or vacuum to remove dirt, dust and debris from flooring surface. Do not use vacuums that contain beater bars or electric brooms with hard plastic bottoms and/or no padding, as these devices may cause discoloration, scratching and loss of sheen.

Mix PR-930 with clean, potable water in a clean mixing container. Adjust dilution rate based on amount of removal required. Apply

cleaner directly to floor with a clean mop, pad or sponge and let stand for 10-20 minutes. Scrub area using a rotary floor machine or auto-scrubbing machine to remove finish. Be sure to use a cleaning pad approved for use with the floor covering, as aggressive pads could damage, mar or diminish the sheen of some flooring products. Maintain a wet surface while scrubbing to avoid damaging flooring product and apply more material as necessary.

Remove cleaning solution with an auto-scrubber or a wet vacuum. Dispose of stripping solution in accordance with local, state and federal disposal regulations. Once removed, rinse flooring surface with clean, cold potable water and a clean mop, pad or sponge.

FOR PROFESSIONAL USE ONLY. PLEASE CONSULT ALL ASSOCIATED TECHNICAL DATA SHEETS, SAFETY DATA SHEETS AND WARRANTY INFORMATION PRIOR TO INSTALLATION.