

Pinnacle Wall Base, 3" No Toe

Manufacturer

Roppe Corporation
 1602 N. Union Street
 P.O. Box 1158
 Fostoria, Ohio USA 44830-1158
 Website - www.roppe.com
 t: (419) 435.8546 tf: (800) 537.9527
 f: (419) 435.1056
 e-mail: sales@roppe.com

Product Description

No matter what the project, 100% PVC free Roppe Pinnacle rubber base is ideal for the job. Pinnacle is the professional's choice because this SBR rubber base is highly durable and extremely flexible, allowing for easy installation around columns, corners and architectural curves.


Features

PVC Free	Extremely Durable & Flexible
Phthalates Free	Will not Shrink, Gap or Cup
Variety of Sizes	Recycleable (IMPACT Program)
FloorScore® Certified	Qualifies for LEED® Credits

Pinnacle Wall Base, 3"

Toe Type:	No Toe
Base Height:	3" (76.2 mm)
Base Thickness:	1/8" (3.2 mm)
Base Length:	48" Sections or 120' ft. Coils
Carton Quantity:	30 pieces or 1 coil
Carton Weight:	28 lbs.

Additional Accessories: Inside and outside factory corners, inside and outside corner blocks, as well as inside and outside micro corner blocks are available to match wall base installations.



Technical Data

LEED v2009 IEQ Credit 4.1: Qualifies
 ASTM F1861 - Resilient Wall Base: Type TS, Group 1, Style A
 ASTM E84 - Flammability: Class B
 ASTM E648 (NFPA 253) - Critical Radiant Flux: Class I,
 > 0.45 W/cm²
 ASTM E662 (NFPA 258) - Smoke Density: Passes, <450

CAN/ULC-S102.2 - Surface Burning: FSR 50, SDS 175
 Acclimation Time: 48 Hours
 Storage & Acclimation Temperature: 65° - 85° F

Adhesives* (Visit our website for complete Adhesive instructions)

AW-510 Acrylic Wet-Set Adhesive

Unit Size: 1 or 4 Gallon Units
 VOC: < 0.1 g/l
 Coverage Rate: 160 sq. ft. per gallon
 Substrate: Porous

WB-600 Acrylic Wall Base Adhesive

Unit Size: 30 oz. Cartridge, 1 Gallon and 4 Gallon Units
 VOC: < 12 g/l
 Trowel Coverage Rate: 180-340 lin. ft. per gallon
 Cartridge Coverage Rate: 30-70 lin. ft. per cartridge
 Substrate: Porous

C-630 Contact Adhesive

Unit Size: 1 Quart
 VOC: 0.0 g/l
 Coverage Rate: 20-40 sq. ft. per unit or 120-140 lin. ft. per unit.
 Substrate: Non-Porous

Installation* (Visit our website for complete Installation instructions)

All material is to be delivered to the installation location in its original packaging with labels intact. The installation area, unboxed wall base and adhesive are to be maintained between 65° (19°C) and 85° (30°C) for at least 48 hours before installation, during installation and thereafter. Proceed with the installation only when the conditions are proper and correct. Inspect all material for proper type and color. A bond test should be performed at least 72 hours prior to the scheduled installation to ensure the surface is suitable and there should be extreme difficulty in removing the wall base from the surface.

Maintenance* (Visit our website for complete Maintenance instructions)

Pinnacle Base can be cleaned with a neutral pH cleaner and a soft wet cloth.

Availability, Cost & Samples

Roppe Flooring products are sold through distribution. To locate the nearest distributor, visit www.roppe.com. or send an email to solutions@roppe.com

Technical Document Support

Additional product resources and technical documents are available online at www.roppe.com. For additional technical support, send an e-mail to solutions@roppe.com

Warranty

Roppe Provides a 2 year Limited Warranty on all Pinnacle Wall Base. For additional information, see associated Warranty documents.

***For complete adhesive, installation & maintenance instructions, visit www.roppe.com**