

## 700 Series Wall Base, 6" No Toe

### Manufacturer

Roppe Corporation  
 1602 N. Union Street  
 P.O. Box 1158  
 Fostoria, Ohio USA 44830-1158  
 Website - [www.roppe.com](http://www.roppe.com)  
 t: (419) 435.8546 tf: (800) 537.9527  
 f: (419) 435.1056  
 e-mail: [sales@roppe.com](mailto:sales@roppe.com)

### Product Description

Our 700 Series wall base is an outstanding selection for any installation. Easier to work with and providing more flexibility than vinyl base products, Roppe's unique blend of thermoplastic rubber and vinyl makes the 700 Series an attractive and economical choice for a variety of applications.

### Features

Extremely Durable and Flexible  
 Will not Shrink, Gap or Cup  
 Recycleable (IMPACT Recycling Program)  
 Qualifies for LEED® Credits  
 FloorScore® Certified

### 700 Series, 6"

Toe Type:	<b>No Toe</b>
Base Height:	<b>6" (152.1 mm)</b>
Base Thickness:	<b>1/8" (3.2 mm)</b>
Base Length:	<b>48" Sections or 120' ft. Coils</b>
Carton Quantity:	<b>30 pieces or 1 coil</b>
Carton Weight:	<b>60 lbs.</b>

**Additional Accessories:** Inside and outside factory corners are available to match wall base installations.



No  
Toe Base

### Technical Data

LEED v2009 IEQ Credit 4.1: Qualifies  
 ASTM F1861 - Resilient Wall Base: Type TP, Group 2, Style A  
 ASTM E648 (NFPA 253) - Critical Radiant Flux: Class I,  
 > 0.45 W/cm<sup>2</sup>  
 ASTM E662 (NFPA 258) - Smoke Density: Passes, <450  
 ASTM E84 - Flammability: Class A

CAN/ULC-S102.2 - Surface Burning: FSR 10, SDS 60  
 Acclimation Time: 48 Hours  
 Storage & Acclimation Temperature: 65° - 85° F

**Adhesives\*** (Visit our website for complete Adhesive instructions)

### AW-510 Acrylic Wet-Set Adhesive

Unit Size: 1 or 4 Gallon Units  
 VOC: < 0.1 g/l  
 Coverage Rate: 160 sq. ft. per gallon  
 Substrate: Porous

### WB-600 Acrylic Wall Base Adhesive

Unit Size: 30 oz. Cartridge, 1 Gallon and 4 Gallon Units  
 VOC: < 12 g/l  
 Trowel Coverage Rate: 180-340 lin. ft. per gallon  
 Cartridge Coverage Rate: 30-70 lin. ft. per cartridge  
 Substrate: Porous

### C-630 Contact Adhesive

Unit Size: 1 Quart  
 VOC: 0.0 g/l  
 Coverage Rate: 20-40 sq. ft. per unit or 120-140 lin. ft. per unit.  
 Substrate: Non-Porous

**Installation\*** (Visit our website for complete Installation instructions)

All material is to be delivered to the installation location in its original packaging with labels intact. The installation area, unboxed wall base and adhesive are to be maintained between 65° (19°C) and 85° (30°C) for at least 48 hours before installation, during installation and thereafter. Proceed with the installation only when the conditions are proper and correct. Inspect all material for proper type and color. A bond test should be performed at least 72 hours prior to the scheduled installation to ensure the surface is suitable and there should be extreme difficulty in removing the wall base from the surface.

**Maintenance\*** (Visit our website for complete Maintenance instructions)

700 Series wall base can be cleaned with a neutral pH cleaner and a soft wet cloth.

### Availability, Cost & Samples

Roppe Flooring products are sold through distribution. To locate the nearest distributor, visit [www.roppe.com](http://www.roppe.com). or send an email to [solutions@roppe.com](mailto:solutions@roppe.com)

### Technical Document Support

Additional product resources and technical documents are available online at [www.roppe.com](http://www.roppe.com). For additional technical support, send an e-mail to [solutions@roppe.com](mailto:solutions@roppe.com)

### Warranty

Roppe Provides a 2 year Limited Warranty on all 700 Series Wall Base. For additional information, see associated Warranty documents.

**\*For complete adhesive, installation & maintenance instructions, visit [www.roppe.com](http://www.roppe.com)**