

Rop-Cord Recycled Rubber Tile

Manufacturer

Roppe Corporation
1602 N. Union Street
P.O. Box 1158
Fostoria, Ohio USA 44830-1158
Website - www.roppe.com
t: (419) 435.8546 tf: (800) 537.9527
f: (419) 435.1056
e-mail: sales@roppe.com

Product Description

Rop-Cord is a durable, slip-resistant flooring product manufactured from recycled automobile tires. Designed for demanding commercial applications, indoors or outdoors. Rop-Cord can also be used in areas that may be subjected to cleats and spikes. Great choice for inclined ramps, walkways, stairwells and airport passenger loading bridges. Available in a durable non-vulcanized and vulcanized version.

Non-Vulcanized Rop-Cord is constructed of strips from a biased ply truck tire that are bonded to a spunbond polyester backing and then buffed to reveal the cord of the tile. It is the cord that provides the appearance of the Rop-Cord. These cords are left natural in the earthtone and then dyed to create the colored appearances.

Vulcanized Rop-Cord is constructed in the same manner with one exception, the strips are bonded to a rubber backing through vulcanization process.

Features

PVC Free	Does Not Require A Finish
Noise-Reducing Material	Excellent Chemical Resistance
Superior Slip Resistance	Qualifies for LEED® Credits
FloorScore® Certified	ADA Complaint for use on ramps



Rop-Cord Recycled Rubber Tile

Nominal Dimensions: 12" x 12" x 9.52 mm
Gauge: 3/8" (9.52 mm)
Backing: Vulcanized or Non-Vulcanized
Finish: Ribbed
Weight Per Carton: ~ 2.1 lbs.
Carton Quantity: 25 tiles
Available Colors: Pine, Indigo, Crimson, Earthtone

Technical Data

LEED v2009 IEQ Credit 4.1: Qualifies
LEED v2009 IEQ Credit 4.3: Qualifies
Recycled Content: 90%, Post-Consumer
ASTM D2859 (FF1-70, 16 CFR 1630) Ignition
Characteristics: Passes
Acclimation Time: 48 Hours
Storage & Acclimation Temperature: 65 ° - 85 ° F

Approved Adhesive* (*Visit our website for complete Adhesive recommendations*)

MS-700 Modified Silane
EW-710 Epoxy Wet Set Adhesive

Installation* (*Visit our website for complete Installation instructions*)

Product is designed for installation in a parquet or quarter-turned fashion. Installation in a linear fashion can cause undesirable effect not covered by the product warranty.

All materials are to be delivered to the installation location within 48 hours of installation in its original packaging with labels intact. Store products in a dry area protected from the weather with temperatures maintained between 65° F (19°C) and 85° F (30°C). DO NOT stack pallets. Remove all plastic wrapping and strapping from the pallets and un-box all material in the installation area at

Maintenance

Refer to the Rop-Cord Maintenance information for detailed instructions on the Roppe Website.

Availability, Cost & Samples

Roppe Flooring products are sold through distribution. To locate the nearest distributor, visit www.roppe.com. or send an email to solutions@roppe.com

Technical Document Support

Additional product resources and technical documents are available online at www.roppe.com. For additional technical support, send an e-mail to solutions@roppe.com

Warranty

Roppe Provides a 5 year Limited Warranty. For additional information, see associated Warranty documents.

***For complete adhesive, installation & maintenance instructions, visit www.roppe.com**