


## #70 Valiant - PV4070

### Manufacturer

Roppe Corporation  
1602 N. Union Street  
P.O. Box 1158  
Fostoria, Ohio USA 44830-1158 Website -  
www.roppe.com  
t: (419) 435.8546 tf: (800) 537.9527  
f: (419) 435.1056  
e-mail: sales@roppe.com

### Product Description

Roppe Contours profiled wall base system is a TP sculpted wall base. Contours base comes in a variety of profiles and is designed for use in both commercial and residential wall base applications. Available in several heights from 3" to 7 3/4" and are designed to match a wide variety of flooring installations and applications requirements.



## #70 Valiant - PV4070

Nominal Height: **4 1/2" (114.3mm)**  
Nominal Thickness: **1/2" (12.7mm)**  
Nominal Length: **8' ft. Sections (2.44m)**  
Carton Quantity: **5 Pieces (40' Total)**

### Technical Data

LEED v2009 IEQ Credit 4.1: **Qualifies**  
ASTM F1861 - Resilient Wall Base: **Type TP, Group 2, Style D**  
ASTM E648 (NFPA 253) - Critical Radiant Flux: **Class I, > 0.45 W/cm<sup>2</sup>**  
ASTM E662 (NFPA 258) - Smoke Density: **Passes, <450**  
ASTM E84 - Flammability: **Class A**  
Acclimation Time: **48 hours**  
Storage & Acclimation Temperature: **65 ° - 85 ° F**

### Approved Adhesive\* (*Visit our website for complete Adhesive recommendations*)

WB-600 Acrylic Wall Base Adhesive  
C-630 Contact Adhesive

### Installation\* (*Visit our website for complete Installation instructions*)

All material is to be delivered to the installation location in its original packaging with labels intact. The installation area, unboxed wall base and adhesive are to be maintained between 65° (19°C) and 85° (30°C) for at least 48 hours before installation, during installation and thereafter. Proceed with the installation only when the conditions are proper and correct. Inspect all material for proper type and color. A bond test should be performed at least 72 hours prior to the scheduled installation to ensure the surface is suitable and there should be extreme difficulty in removing the wall base from the surface.

### Maintenance\* (*Visit our website for complete Maintenance instructions*)

Contours can be cleaned with a neutral pH cleaner and a soft wet cloth.

### Technical Document Support

Additional product resources and technical documents are available online at [www.roppe.com](http://www.roppe.com). For additional technical support, send an e-mail to [solutions@rhctechincal.com](mailto:solutions@rhctechincal.com)

### Warranty

Roppe Provides a 2 year Limited Warranty. For additional information, see associated Warranty documents.

**\*For complete adhesive, installation & maintenance instructions, visit [www.roppe.com](http://www.roppe.com)**