

Nominal Dimensions	2 1/2" (63.5 mm) x 48" (1.22 m) x 1/8" (3.2 mm) 2 1/2" (63.5 mm) x 120' (36.58 m) x 1/8" (3.2 mm)
ASTM F1861 - Resilient Wall Base	Type TP, Group 2, Styles A
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, ≥ 0.45 W/cm ²
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM E84 - Flammability	Class A
CAN/ULC-S102.2 - Surface Burning	10 Flame Spread Rating 60 Smoke Developed Classification
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, Additional chemicals available via chart
ASTM F1515 - Light Stability	Excellent, $\Delta E \leq 8$
Acclimation Time	48 Hours, see installation instructions for details
Service & Storage Temperature	65° - 85° F, see installation instructions for details
Sustainability Information	Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification* NSF/ANSI 332 Certified Platinum* HPD Available*
Warranty	5 Year Commercial, see warranty document for details
Recommended Adhesives	Excelsior WB-600, Wall Base Adhesive Excelsior C-630, Contact Adhesive
Technical Support	solutions@rhctechical.com
Product Support	sales@roppe.com
Technical Documentation	www.roppe.com

*certificate or document available on website



No
Toe Base

