

<b>Nominal Dimensions</b>	6" (15.2 cm) Height x 8' (2.4 m) Length
<b>Coverage Over Flooring Expansion Gap</b>	3/8" (9.5 cm)
<b>ASTM F1861 - Resilient Wall Base</b>	Type TP, Group 2, Style D
<b>ASTM E648 (NFPA 253) - Critical Radiant Flux</b>	Class 1, $\geq 0.45$ W/cm <sup>2</sup>
<b>ASTM E662 (NFPA 258) - Smoke Density</b>	Passes, $\leq 450$
<b>ASTM E84 - Flammability</b>	Class A
<b>CAN/ULC-S102.2 - Surface Burning</b>	10 Flame Spread Rating 60 Smoke Developed Classification
<b>ASTM F925 - Chemical Resistance</b>	Excellent with chemicals listed in standard, Additional chemicals available via chart
<b>ASTM F1515 - Light Stability</b>	Excellent, $\Delta E \leq 8$
<b>Acclimation Time</b>	48 Hours, see installation instructions for details
<b>Service &amp; Storage Temperature</b>	65° - 85° F, see installation instructions for details
<b>Sustainability Information</b>	Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification* NSF/ANSI 332 Certified Platinum* HPD Available*
<b>Warranty</b>	10 Year Commercial, see warranty document for details
<b>Recommended Adhesives</b>	Excelsior WB-600, Wall Base Adhesive Excelsior C-630, Contact Adhesive
<b>Technical Support</b>	<a href="mailto:solutions@rhctechnical.com">solutions@rhctechnical.com</a>
<b>Product Support</b>	<a href="mailto:sales@roppe.com">sales@roppe.com</a>
<b>Technical Documentation</b>	<a href="http://www.roppe.com">www.roppe.com</a>

\*certificate or document available on website

