

Nominal Dimensions

Covers 1/4" (6.4 mm) From Wall

<i>Simplicity #00</i>	4" (10.2 cm) Height x 8' (2.4 m) Length
<i>Serenity #10</i>	4" (10.2 cm) Height x 8' (2.4 m) Length
<i>Novel #45</i>	7 3/4" (19.7 cm) Height x 8' (2.4 m) Length
<i>Valiant #70</i>	4 1/2" (11.4 cm) Height x 8' (2.4 m) Length
<i>Divine #80</i>	4 1/2" (11.4 cm) Height x 8' (2.4 m) Length
<i>Fashion #85</i>	4 1/4" (10.8 cm) Height x 8' (2.4 m) Length
<i>Fashion #85</i>	6 1/4" (15.9 cm) Height x 8' (2.4 m) Length

Covers 3/8" (9.5 mm) From Wall

<i>Novel #45</i>	4 1/2" (11.4 cm) Height x 8' (2.4 m) Length
<i>Nobility #55</i>	5 1/2" (14 cm) Height x 8' (2.4 m) Length
<i>Candid #60</i>	3" (7.6 cm) Height x 8' (2.4 m) Length
<i>Candid #60</i>	4 1/4" (10.8 cm) Height x 8' (2.4 m) Length
<i>Vertical #65</i>	3" (7.6 cm) Height x 8' (2.4 m) Length
<i>Vertical #65</i>	4 5/8" (11.7 cm) Height x 8' (2.4 m) Length
<i>Vertical #65</i>	6" (15.2 cm) Height x 8' (2.4 m) Length
<i>Intrigue #90</i>	4" (10.5 cm) Height x 8' (2.4 m) Length
<i>Intrigue #90</i>	5 1/2" (14 cm) Height x 8' (2.4 m) Length

Covers 1/2" (12.7 mm) From Wall

<i>Simplicity Bold #05</i>	4 1/2" (11.4 cm) Height x 8' (2.4 m) Length
----------------------------	---------------------------------------------

12 Foot (3.7 m) & 40 Foot (12.2 m) Lengths

<i>Quarter Round #350</i>	#350 - 1/2" (12.7 mm) Height x 1/2" (12.7 mm) Width
---------------------------	-----------------------------------------------------

ASTM F1861 - Resilient Wall Base	Type TP, Group 2, Style D
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, ≥ 0.45 W/cm ²
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM E84 - Flammability	Class A
CAN/ULC-S102.2 - Surface Burning	10 Flame Spread Rating 60 Smoke Developed Classification
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, Additional chemicals available via chart
ASTM F1515 - Light Stability	Excellent, $\Delta E \leq 8$
Acclimation Time	48 Hours, see installation instructions for details
Service & Storage Temperature	65° - 85° F, see installation instructions for details

Sustainability Information	<p>Contributes to LEED v4/4.1</p> <p>Meets CA 01350 Requirements</p> <p>FloorScore Certification*</p> <p>NSF/ANSI 332 Certified Platinum*</p> <p>HPD Available*</p>
Warranty	10 Year Commercial, see warranty document for details
Recommended Adhesives	<p>Excelsior WB-600, Wall Base Adhesive</p> <p>Excelsior C-630, Contact Adhesive</p>
Technical Support	solutions@rhctechnical.com
Product Support	sales@roppe.com
Technical Documentation	www.roppe.com

**certificate or document available on website*