

Nominal Dimensions	4" (10.2 cm) Height x 120' (36.6 m) Length
Coverage Over Flooring Expansion Gap	3/8" (9.5 mm)
ASTM F1861 - Resilient Wall Base	Type TS, Group 1, Styles D
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM E84 - Flammability	Class B
CAN/ULC-S102.2 - Surface Burning	50 Flame Spread Rating, 175 Smoke Developed Classification
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, additional chart available
Sustainability Information	<p>Made in the U.S.A.</p> <p>Meets Buy America Act (49 CFR Part 661)</p> <p>Meets Buy American Act (41 USC §§ 8301-8303)</p> <p>Contributes to LEED v4/4.1</p> <p>NSF/ANSI 332 Platinum Certification</p> <p>GREENGUARD Gold Certification</p> <p>FloorScore Certification</p> <p>Meets CA 01350 Requirements</p> <p>Meets CHPS Requirements</p> <p>EPD Available</p> <p>Red List Chemical Free</p> <p>Contains No Recycled Content</p> <p>HPD Available</p>
Acclimation Time	48 Hours
Service & Storage Temperature	65° - 85° F
<i>See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, & acclimation procedures</i>	
Product Warranty	10 Year Commercial
<i>See product warranty for full details regarding limitations & warranty coverage</i>	
Approved Adhesives	<p>Excelsior WB-600, Wall Base Adhesive</p> <p>Excelsior C-630, Contact Adhesive</p>
<i>See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, & acclimation procedures</i>	
Technical Support	solutions@rhctechnical.com
Product Support	sales@roppe.com
Technical Documentation	www.roppe.com

#20 Draft Pinnacle Plus Wall Base

PRODUCT SUBMITTAL



Attach Color Sample Here