

<b>Nominal Dimensions</b>	4" (10.2 cm) Height x 60' (18.3 m) Length
<b>Coverage Over Flooring Expansion Gap</b>	3/16" (4.8 mm)
<b>ASTM F1861 - Resilient Wall Base</b>	Type TS, Group 1, Styles D
<b>ASTM E648 (NFPA 253) - Critical Radiant Flux</b>	Class 1, $\geq 0.45 \text{ W/cm}^2$
<b>ASTM E662 (NFPA 258) - Smoke Density</b>	Passes, $\leq 450$
<b>ASTM E84 - Flammability</b>	Class B
<b>CAN/ULC-S102.2 - Surface Burning</b>	50 Flame Spread Rating, 175 Smoke Developed Classification
<b>ASTM F925 - Chemical Resistance</b>	Excellent with chemicals listed in standard, additional chart available
<b>Sustainability Information</b>	<p>Made in the U.S.A.</p> <p>Meets Buy America Act (49 CFR Part 661)</p> <p>Meets Buy American Act (41 USC §§ 8301-8303)</p> <p>Contributes to LEED v4/4.1</p> <p>NSF/ANSI 332 Platinum Certification</p> <p>GREENGUARD Gold Certification</p> <p>FloorScore Certification</p> <p>Meets CA 01350 Requirements</p> <p>Meets CHPS Requirements</p> <p>EPD Available</p> <p>Red List Chemical Free</p> <p>Contains No Recycled Content</p> <p>HPD Available</p>
<b>Acclimation Time</b>	48 Hours
<b>Service &amp; Storage Temperature</b>	65° - 85° F
<i>See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, &amp; acclimation procedures</i>	
<b>Product Warranty</b>	10 Year Commercial
<i>See product warranty for full details regarding limitations &amp; warranty coverage</i>	
<b>Approved Adhesives</b>	<p>Excelsior WB-600, Wall Base Adhesive</p> <p>Excelsior C-630, Contact Adhesive</p>
<i>See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, &amp; acclimation procedures</i>	
<b>Technical Support</b>	solutions@rhctechnical.com
<b>Product Support</b>	sales@roppe.com
<b>Technical Documentation</b>	www.roppe.com

