

<b>Nominal Dimensions</b>	5 1/2" (14 cm) Height x 8' (2.4 m) Length
<b>Coverage Over Flooring Expansion Gap</b>	3/8" (9.5 mm)
<b>ASTM F1861 - Resilient Wall Base</b>	Type TS, Group 1, Styles D
<b>ASTM E648 (NFPA 253) - Critical Radiant Flux</b>	Class 1, $\geq 0.45 \text{ W/cm}^2$
<b>ASTM E662 (NFPA 258) - Smoke Density</b>	Passes, $\leq 450$
<b>ASTM E84 - Flammability</b>	Class B
<b>CAN/ULC-S102.2 - Surface Burning</b>	50 Flame Spread Rating, 175 Smoke Developed Classification
<b>ASTM F925 - Chemical Resistance</b>	Excellent with chemicals listed in standard, additional chart available

<b>Sustainability Information</b>	Made in the U.S.A.
	Meets Buy America Act (49 CFR Part 661)
	Meets Buy American Act (41 USC §§ 8301-8303)
	Contributes to LEED v4/4.1
	NSF/ANSI 332 Platinum Certification
	GREENGUARD Gold Certification
	FloorScore Certification
	Meets CA 01350 Requirements
	Meets CHPS Requirements
	EPD Available
	Red List Chemical Free
	Contains No Recycled Content
	HPD Available

<b>Acclimation Time</b>	48 Hours
<b>Service &amp; Storage Temperature</b>	65° - 85° F

See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, & acclimation procedures

<b>Product Warranty</b>	10 Year Commercial
-------------------------	--------------------

See product warranty for full details regarding limitations & warranty coverage

<b>Approved Adhesives</b>	Excelsior WB-600, Wall Base Adhesive
	Excelsior C-630, Contact Adhesive

See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, & acclimation procedures

<b>Technical Support</b>	solutions@rhctechnical.com
<b>Product Support</b>	sales@roppe.com
<b>Technical Documentation</b>	www.roppe.com

# #55 Nobility Pinnacle Plus Wall Base

PRODUCT SUBMITTAL



Attach Color Sample Here