

Nominal Dimensions	4" (10.2 cm) Height x 60' (18.3 m) Length
Coverage Over Flooring Expansion Gap	3/8" (9.5 mm)
ASTM F1861 - Resilient Wall Base	Type TS, Group 1, Styles D
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM E84 - Flammability	Class B
CAN/ULC-S102.2 - Surface Burning	50 Flame Spread Rating, 175 Smoke Developed Classification
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, additional chart available

Sustainability Information	Made in the U.S.A.
	Meets Buy America Act (49 CFR Part 661)
	Meets Buy American Act (41 USC §§ 8301-8303)
	Contributes to LEED v4/4.1
	NSF/ANSI 332 Platinum Certification
	GREENGUARD Gold Certification
	FloorScore Certification
	Meets CA 01350 Requirements
	Meets CHPS Requirements
	EPD Available
	Red List Chemical Free
	Contains No Recycled Content
	HPD Available

Acclimation Time	48 Hours
Service & Storage Temperature	65° - 85° F

See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, & acclimation procedures

Product Warranty	10 Year Commercial
-------------------------	--------------------

See product warranty for full details regarding limitations & warranty coverage

Approved Adhesives	Excelsior WB-600, Wall Base Adhesive
	Excelsior C-630, Contact Adhesive

See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, & acclimation procedures

Technical Support	solutions@rhctechnical.com
Product Support	sales@roppe.com
Technical Documentation	www.roppe.com

#90 *Intrigue Pinnacle Plus Wall Base*

PRODUCT SUBMITTAL

