

Nominal Dimensions

Covers 3/16" (4.8 mm) From Wall

Simplicity #00	4" (10.2 cm) Height x 60' (18.3 m) Length
Serenity #10	4" (10.2 cm) Height x 60' (18.3 m) Length
Impulse #15	5 1/4" (13.3 cm) Height x 60' (18.3 m) Length
Classic #25	4 9/16" (11.6 cm) Height x 60' (18.3 m) Length
Sleek #35	4 9/16" (11.6 cm) Height x 60' (18.3 m) Length
Impressions #50	4" (10.2 cm) Height x 60' (18.3 m) Length

Covers 1/4" (6.4 mm) From Wall

Contrive #05	2 1/2" (6.4 cm) Height x 60' (18.3 m) Length
Fashion #85	4 1/4" (10.8 cm) Height x 60' (18.3 m) Length

Covers 3/8" (9.5 mm) From Wall

Draft #20	4" (10.2 cm) Height x 120' (36.6 m) Length
Sketch #30	4" (10.2 cm) Height x 120' (36.6 m) Length
Nobility #55	5 1/2" (14 cm) Height x 8' (2.4 m) Length
Vertical #65	4 5/8" (11.7 cm) Height x 8' (2.4 m) Length
Level #75	3" (7.6 cm) Height x 8' (2.4 m) Length
Intrigue #90	4" (10.2 cm) Height x 60' (18.3 m) Length
Invent #95	5 1/2" (14 cm) Height x 60' (18.3 m) Length

Corner Blocks & Micro Corner Blocks available
 Inside Corners & Outside Corners are not available
 Recommended to Miter Corners onsite
 Some profiles may be wrapped with proper installation techniques

ASTM F1861 - Resilient Wall Base	Type TS, Group 1, Styles D
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM E84 - Flammability	Class B
CAN/ULC-S102.2 - Surface Burning	50 Flame Spread Rating, 175 Smoke Developed Classification
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, additional chart available

Sustainability Information

Made in the U.S.A.
 Meets Buy America Act (49 CFR Part 661)
 Meets Buy American Act (41 USC §§ 8301-8303)
 Contributes to LEED v4/4.1
 NSF/ANSI 332 Platinum Certification
 GREENGUARD Gold Certification

Sustainability Information...

FloorScore Certification
 Meets CA 01350 Requirements
 Meets CHPS Requirements
 EPD Available
 Red List Chemical Free
 Contains No Recycled Content
 HPD Available

Acclimation Time 48 Hours
Service & Storage Temperature 65° - 85° F

See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, & acclimation procedures

Product Warranty 10 Year Commercial

See product warranty for full details regarding limitations & warranty coverage

Approved Adhesives Excelsior WB-600, Wall Base Adhesive
 Excelsior C-630, Contact Adhesive

See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, & acclimation procedures

Technical Support solutions@rhctechnical.com
Product Support sales@roppe.com
Technical Documentation www.roppe.com