

Nominal Dimensions

Covers 3/16" (4.8 mm) From Wall

<i>Simplicity #00</i>	4" (10.2 cm) Height x 60' (18.3 m) Length
<i>Serenity #10</i>	4" (10.2 cm) Height x 60' (18.3 m) Length
<i>Impulse #15</i>	5 1/4" (13.3 cm) Height x 60' (18.3 m) Length
<i>Classic #25</i>	4 9/16" (11.6 cm) Height x 60' (18.3 m) Length
<i>Sleek #35</i>	4 9/16" (11.6 cm) Height x 60' (18.3 m) Length
<i>Impressions #50</i>	4" (10.2 cm) Height x 60' (18.3 m) Length

Covers 1/4" (6.4 mm) From Wall

<i>Contrive #05</i>	2 1/2" (6.4 cm) x 60' (18.3 m) Length
<i>Fashion #85</i>	4 1/4" (10.8 cm) x 60' (18.3 m) Length

Covers 3/8" (9.5 mm) From Wall

<i>Draft #20</i>	4" (10.2 cm) Height x 120' (36.6 m) Length
<i>Sketch #30</i>	4" (10.2 cm) Height x 120' (36.6 m) Length
<i>Nobility #55</i>	5 1/2" (14 cm) x 8' (2.4 m) Length
<i>Vertical #65</i>	4 5/8" (11.7 cm) x 8' (2.4 m) Length
<i>Level #75</i>	3" (7.6 cm) x 8' (2.4 m) Length
<i>Intrigue #90</i>	4" (10.2 cm) Height x 60' (18.3 m) Length
<i>Invent #95</i>	5 1/2" (14 cm) Height x 60' (18.3 m) Length

ASTM F1861 - Resilient Wall Base	Type TS, Group 1, Style D
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, ≥ 0.45 W/cm ²
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM E84 - Flammability	Class B
CAN/ULC-S102.2 - Surface Burning	50 Flame Spread Rating 175 Smoke Developed Classification
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, Additional chemicals available via chart
ASTM F1515 - Light Stability	Excellent, $\Delta E \leq 8$
Acclimation Time	48 Hours, see installation instructions for details
Service & Storage Temperature	65° - 85° F, see installation instructions for details

Sustainability Information	Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification* NSF/ANSI 332 Certified Platinum* HPD Available* Recyclable Through Roppe Impact Program
Warranty	10 Year Commercial, see warranty document for details
Recommended Adhesives	Excelsior WB-600, Wall Base Adhesive Excelsior C-630, Contact Adhesive
Technical Support	solutions@rhctechnical.com
Product Support	sales@roppe.com
Technical Documentation	www.roppe.com

**certificate or document available on website*