

---

<b>Nominal Dimensions</b>	2 1/2" (6.4 cm)
	3" (7.6 cm)
	3 1/2" (8.9 cm)
	4" (10.2 cm)
	4 1/2" (11.4 cm)
	5" (12.7 cm)
	5 1/2" (13.9 cm)
	6" (15.2 cm)

*Pinnacle Wall Base Products available in 1/8" thickness only*  
*Cove Base & No Toe Base available in all heights in 48" & 120' lengths*  
*Butt Toe, Long Toe, and Sanitary Toe Profiles available in 4" height x 48" length only*  
*Outside Corners & No Toe Outside Corners available in 2 1/2", 4", & 6" sizes only*  
*Inside Corners available in 2 1/2", 4", & 6" sizes only*  
*Outside Corners for 4" Long Toe & Sanitary Base available*

---

<b>ASTM F1861 - Resilient Wall Base</b>	Type TS, Group 1, Styles A, B, & C
<b>ASTM E648 (NFPA 253) - Critical Radiant Flux</b>	Class 1, $\geq 0.45 \text{ W/cm}^2$
<b>ASTM E662 (NFPA 258) - Smoke Density</b>	Passes, $\leq 450$
<b>ASTM E84 - Flammability</b>	Class B
<b>CAN/ULC-S102.2 - Surface Burning</b>	50 Flame Spread Rating, 175 Smoke Developed Classification
<b>ASTM F925 - Chemical Resistance</b>	Excellent with chemicals listed in standard, additional chart available

---

<b>Sustainability Information</b>	Made in the U.S.A.
	Meets Buy America Act (49 CFR Part 661)
	Meets Buy American Act (41 USC §§ 8301-8303)
	Contributes to LEED v4/4.1
	NSF/ANSI 332 Platinum Certification
	GREENGUARD Gold Certification
	FloorScore Certification
	Meets CA 01350 Requirements
	Meets CHPS Requirements
	EPD Available
	Red List Chemical Free
	Contains No Recycled Content

---

<b>Acclimation Time</b>	48 Hours
<b>Service &amp; Storage Temperature</b>	65° - 85° F

See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, & acclimation procedures

---

**Product Warranty** 5 Year Commercial

*See product warranty for full details regarding limitations & warranty coverage*

---

**Approved Adhesives** Excelsior WB-600, Wall Base Adhesive  
Excelsior C-630, Contact Adhesive

*See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, & acclimation procedures*

---

**Technical Support** solutions@rhctechnical.com

**Product Support** sales@roppe.com

**Technical Documentation** www.roppe.com