

Nominal Dimensions	2 1/2" (6.4 cm) x 48" (1.22 m) x 1/8" (3.2 mm) 2 1/2" (6.4 cm) x 120' (36.58 m) x 1/8" (3.2 mm)
ASTM F1861 - Resilient Wall Base	Type TS, Group 1, Style B
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM E84 - Flammability	Class B
CAN/ULC-S102.2 - Surface Burning	50 Flame Spread Rating, 175 Smoke Developed Classification
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, additional chart available
Sustainability Information	Made in the U.S.A. Meets Buy America Act (49 CFR Part 661) Meets Buy American Act (41 USC §§ 8301-8303) Contributes to LEED v4/4.1 NSF/ANSI 332 Platinum Certification GREENGUARD Gold Certification FloorScore Certification Meets CA 01350 Requirements Meets CHPS Requirements EPD Available Red List Chemical Free Contains No Recycled Content HPD Available
Acclimation Time	48 Hours
Service & Storage Temperature	65° - 85° F
<i>See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, & acclimation procedures</i>	
Product Warranty	5 Year Commercial
<i>See product warranty for full details regarding limitations & warranty coverage</i>	
Approved Adhesives	Excelsior WB-600, Wall Base Adhesive Excelsior C-630, Contact Adhesive
<i>See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, & acclimation procedures</i>	
Technical Support	solutions@rhctechnical.com
Product Support	sales@roppe.com
Technical Documentation	www.roppe.com

