

|  |   |
|--|---|
| <b>Nominal Dimensions</b>  | 6" (15.2 cm) x 48" (1.22 m) x 1/8" (3.2 mm)<br>6" (15.2 cm) x 120' (36.58 m) x 1/8" (3.2 mm)  |
| <b>ASTM F1861 - Resilient Wall Base</b>  | Type TS, Group 1, Style B   |
| <b>ASTM E648 (NFPA 253) - Critical Radiant Flux</b>  | Class 1, $\geq 0.45 \text{ W/cm}^2$   |
| <b>ASTM E662 (NFPA 258) - Smoke Density</b>  | Passes, $\leq 450$  |
| <b>ASTM E84 - Flammability</b>   | Class B   |
| <b>CAN/ULC-S102.2 - Surface Burning</b>  | 50 Flame Spread Rating, 175 Smoke Developed Classification  |
| <b>ASTM F925 - Chemical Resistance</b>   | Excellent with chemicals listed in standard, additional chart available   |
| <b>Sustainability Information</b>  | Made in the U.S.A.<br><br>Meets Buy America Act (49 CFR Part 661)<br>Meets Buy American Act (41 USC §§ 8301-8303)<br><br>Contributes to LEED v4/4.1<br>NSF/ANSI 332 Platinum Certification<br>GREENGUARD Gold Certification<br>FloorScore Certification<br><br>Meets CA 01350 Requirements<br>Meets CHPS Requirements<br><br>EPD Available<br><br>Red List Chemical Free<br>Contains No Recycled Content<br><br>HPD Available |
| <b>Acclimation Time</b>  | 48 Hours  |
| <b>Service &amp; Storage Temperature</b>   | 65° - 85° F   |
| <i>See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, &amp; acclimation procedures</i> |   |
| <b>Product Warranty</b>  | 5 Year Commercial   |
| <i>See product warranty for full details regarding limitations &amp; warranty coverage</i>   |   |
| <b>Approved Adhesives</b>  | Excelsior WB-600, Wall Base Adhesive<br>Excelsior C-630, Contact Adhesive   |
| <i>See Installation document for full installation details regarding approved substrates, substrate preparation, job site conditions, &amp; acclimation procedures</i> |   |
| <b>Technical Support</b>   | solutions@rhctechnical.com  |
| <b>Product Support</b>   | sales@roppe.com   |
| <b>Technical Documentation</b>   | www.roppe.com   |

