



# Rop-Cord Recycled Rubber Tile

TECHNICAL DATA

<b>Finish</b>	Ribbed Tufted Surface
<b>Nominal Dimensions</b>	12" (30.4 cm) x 12" (30.4 cm) x 3/8" (9.5 mm) (Nominal)
<b>Backing</b>	Vulcanized or Non-Vulcanized
<b>ASTM D2859 - Ignition Characteristics</b>	Passes, (FF1-70, 16 CFR 1630)
<b>ASTM E662 (NFPA 258) - Smoke Density</b>	Passes, ≤ 450
<b>Acclimation Time</b>	48 Hours
<b>Service &amp; Storage Temperature</b>	60° - 85° F

See installation document for full installation details regarding approved substrates, job site conditions and acclimation procedures.

<b>Product Limitations</b>	<p>Due to the recycled nature of this product, color variation can be present from piece to piece.</p> <p>Outdoor Installation, Exposure to Sunlight, and Foot Traffic will cause discoloration and the material to fade to the natural color due to the process of dying the material. It will resort back to the natural color of the tire cord. We do not recommend the application of Dyes to re-color product after fading.</p> <p>Material installed in outdoor application or indoors within 20' of entryways must be the Vulcanized product and we recommend the Earthtone color.</p> <p>Non-Vulcanized material is for indoor applications only, not recommended within 20' of entryways.</p>
----------------------------	--

<b>Product Warranty</b>	5 Year Commercial Warranty
-------------------------	----------------------------

See product warranty for full details regarding limitations and warranty coverage.

<b>Recommended Adhesives</b>	<p>Excelsior PS-525, Modified Pressure Sensitive (<b>ONLY</b> approved for Non-Vulcanized Indoor Installations)</p> <p>Excelsior U-705, Urethane Wet-Set</p> <p>Excelsior EW-710, Urethane Enhanced Epoxy Adhesive</p>
------------------------------	--

<b>Attributes &amp; Certifications</b>	<p>Made in the U.S.A.</p> <p>Meets Buy America Act (49 CFR Part 661, 49 U.S.C. 5323)</p> <p>Meets Buy American Act (7 CFR Part 1787, 41 U.S.C 8301-8305)</p> <p>Meets Federal Acquisition Regulation (FAR 52.225-9)</p> <p>Contributes to LEED v4/4.1</p> <p>90% Post-Consumer Recycled Content</p>
--	---

<b>Technical Support</b>	<a href="mailto:solutions@rhctechical.com">solutions@rhctechical.com</a>
--------------------------	--

<b>Product Support</b>	<a href="mailto:sales@roppe.com">sales@roppe.com</a>
------------------------	--

<b>Technical Documentation</b>	<a href="http://www.roppe.com">www.roppe.com</a>
--------------------------------	--