

<b>Nominal Dimensions</b>	12" (30.5 cm) x 12" (30.5 cm) x 3/8" (9.5 mm)
<b>Finish</b>	Ribbed Tufted Surface
<b>Backing</b>	Vulcanized* Non-Vulcanized**
<b>ASTM D2859 (FF1-70, 16 CFR 1630) - Ignition Characteristics</b>	Passes
<b>Acclimation Time</b>	48 Hours, see installation instructions for details
<b>Service &amp; Storage Temperature</b>	65° - 85° F, see installation instructions for details
<b>Sustainability Information</b>	Contributes to LEED v4/4.1 90% Post-Consumer Recycled Content
<b>Warranty</b>	5 Year Commercial; see warranty document for details
<b>Recommended Adhesives</b>	Excelsior MS-700, Modified Silane Wet-Set Excelsior U-705, Urethane Wet-Set
<b>Technical Support</b>	<a href="mailto:solutions@rhctechnical.com">solutions@rhctechnical.com</a>
<b>Product Support</b>	<a href="mailto:sales@roppe.com">sales@roppe.com</a>
<b>Technical Documentation</b>	<a href="http://www.roppe.com">www.roppe.com</a>

\*vulcanized must be used for outdoors or within 20' of entryway

\*\*non-vulcanized is for interior use only