

Nominal Dimensions	12" (30.5 cm) x 12" (30.5 cm) x 1/8" (3.2 mm) 12" (30.5 cm) x 12" (30.5 cm) x 3/16" (4.8 mm) 19 11/16" (50 cm) x 19 11/16" (50 cm) x 1/8" (3.2 mm) 19 11/16" (50 cm) x 19 11/16" (50 cm) x 3/16" (4.8 mm) 19 11/16" (50 cm) x 19 11/16" (50 cm) x 13/64" (5.2 mm) 24" (61 cm) x 24" (61 cm) x 0.080" (2 mm) 27" (68.6 cm) x 27" (68.6 cm) x 1/8" (3.2 mm) 36" (91.4 cm) x 36" (94.1 cm) x 1/8" (3.2 mm)
Finishes	Smooth, Slate, Low Profile Raised, Textured, Raised Square, Hammered, Raised Circular, Dimensions Crackle, Dimensions Random, Dimensions Stripe
ASTM F1344 - Rubber Floor Tile	Type I A & B, Grade 1
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM D2240 - Durometer Hardness Indention	≥ 85 Shore A
CAN/ULC-S102.2 - Surface Burning	115 Flame Spread Rating 275 Smoked Developed Classification
ASTM D2047 - Static Coefficient of Friction	≥ 0.80
ASTM F970 - Static Load Resistance	Passes, < 0.005 " Indentation after 250 psi
ASTM F970 - Static Load Resistance (Modified)	Passes, < 0.005 " Indentation after 1,100 psi
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, Additional chemicals available via chart
ASTM F1514 - Heat Stability	Excellent, $\Delta E \leq 8$
ASTM F3389 - Abrasion Resistance	Excellent, $\leq 1 \text{ g}$ loss after 1,000 cycles
ASTM G21 - Resistance to Fungi	Excellent
ASTM E492/E989 – Impact Sound Transmission	IIC 51 (6" Concrete, Drop Ceiling Assembly)
ASTM E90/E413 – Airborne Sound Transmission	STC 63 (6" Concrete, Drop Ceiling Assembly)
ASTM E2179 – Effectiveness of Floor on Impact Sound Transmission	Δ IIC 9
Acclimation Time	48 Hours, see installation instructions for details
Service & Storage Temperature	65° - 85° F, see installation instructions for details
Sustainability Information	Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification* NSF/ANSI 332 Platinum Certification* GREENGUARD Gold Certification*

Sustainability Information Continued	EPD Available* HPD Available* Red List Chemical Free Recyclable through the Roppe Impact Program
Warranty	10 Year Commercial; see warranty document for details
Recommended Adhesives	Excelsior SP-500, Acrylic Aerosol Excelsior AP-520, Acrylic Roll-On Pressure Sensitive Excelsior AW-510, Acrylic Wet-Set Excelsior MS-700, Modified Silane Wet-Set Excelsior U-705, Urethane Wet-Set
Technical Support	solutions@rhctechnical.com
Product Support	sales@roppe.com
Technical Documentation	www.roppe.com

**certificate or document available on website*