

Nominal Dimensions	Various Lengths from 36" - 108" depending upon style
Finish	Smooth, Ribbed, Milled, Textured, & Raised Disc
Nose Configuration	Round Nose, Square Nose, & Square Adjustable Nose
ASTM F2169 - Resilient Stair Treads	Type TS, Class 1 & 2, Group 1 & 2, Grade 1
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
CAN/ULC-S102.2 - Surface Burning	115 Flame Spread Rating 275 Smoke Developed Classification
ASTM D2047 - Static Coefficient of Friction	≥ 0.80
ASTM F925 - Chemical Resistance	Petroleum Hydrocarbons, Excellent* Excellent with chemicals listed in standard, Additional chemicals available via chart Not to be used with Vegetable or Animal based Fats & Oils**
Available Abrasive Strip Colors	Safety Yellow, Black, Pebble White, Ocean Gray, Teak Brown, Beige, Galley Red, & Glow Strip
Acclimation Time	48 Hours, see installation instructions for details
Service & Storage Temperature	65° - 85° F, see installation instructions for details
Sustainability Information	Red List Chemical Free Recyclable through the Roppe Impact Program
Warranty	5 Year; see warranty document for details
Recommended Adhesives	Excelsior EN-610, Epoxy Nose Filler Excelsior U-705, Urethane Wet-Set
Technical Support	solutions@rhctechnical.com
Product Support	sales@roppe.com
Technical Documentation	www.roppe.com

*material designed to withstand exposure for a reasonable time to allow the area to be cleaned properly to remove petroleum hydrocarbons

**material not designed for exposure to vegetable or animals fats and oils or use in commercial kitchens