

<b>Nominal Dimensions</b>	12" (30.5 cm) x 12" (30.5 cm) x 1/8" (3.2 mm) 12" (30.5 cm) x 12" (30.5 cm) x 3/16" (4.8 mm) 19 11/16" (50 cm) x 19 11/16" (50 cm) x 1/8" (3.2 mm)* 19 11/16" (50 cm) x 19 11/16" (50 cm) x 3/16" (4.8 mm)
<b>Finishes</b>	*Textured, *Hammered, Smooth
<b>ASTM F1344 - Rubber Floor Tile</b>	Type I A & B, Grade 1
<b>ASTM E648 (NFPA 253) - Critical Radiant Flux</b>	Class 1, $\geq 0.45 \text{ W/cm}^2$
<b>ASTM E662 (NFPA 258) - Smoke Density</b>	Passes, $\leq 450$
<b>ASTM D2240 - Durometer Hardness Indention</b>	$\geq 85$ Shore A
<b>CAN/ULC-S102.2 - Surface Burning</b>	115 Flame Spread Rating 275 Smoked Developed Classification
<b>ASTM D2047 - Static Coefficient of Friction</b>	$\geq 0.80$
<b>ASTM F970 - Static Load Resistance</b>	Passes, $< 0.005$ " Indentation after 250 psi
<b>ASTM F970 - Static Load Resistance (Modified)</b>	Passes, $< 0.005$ " Indentation after 1,100 psi
<b>ASTM F925 - Chemical Resistance</b>	Excellent with chemicals listed in standard, Additional chemicals available via chart
<b>ASTM F1514 - Heat Stability</b>	Excellent, $\Delta E \leq 8$
<b>ASTM F3389 - Abrasion Resistance</b>	Excellent, $\leq 1$ g loss after 1,000 cycles
<b>ASTM G21 - Resistance to Fungi</b>	Excellent
<b>ASTM E492/E989 – Impact Sound Transmission</b>	IIC 51 (6" Concrete, Drop Ceiling Assembly)
<b>ASTM E90/E413 – Airborne Sound Transmission</b>	STC 63 (6" Concrete, Drop Ceiling Assembly)
<b>ASTM E2179 – Effectiveness of Floor on Impact Sound Transmission</b>	$\Delta$ IIC 9
<b>Acclimation Time</b>	48 Hours, see installation instructions for details
<b>Service &amp; Storage Temperature</b>	65° - 85° F, see installation instructions for details
<b>Sustainability Information</b>	Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification** NSF/ANSI 332 Platinum Certification** GREENGUARD Gold Certification** 13% BioBased Content Certification EPD Available** HPD Available** Red List Chemical Free Recyclable through the Roppe Impact Program

<b>Warranty</b>	10 Year Commercial; see warranty document for details
<b>Recommended Adhesives</b>	Excelsior SP-500, Acrylic Aerosol Excelsior AP-520, Acrylic Roll-On Pressure Sensitive Excelsior AW-510, Acrylic Wet-Set Excelsior MS-700, Modified Silane Wet-Set Excelsior U-705, Urethane Wet-Set
<b>Technical Support</b>	<a href="mailto:solutions@rhctechnical.com">solutions@rhctechnical.com</a>
<b>Product Support</b>	<a href="mailto:sales@roppe.com">sales@roppe.com</a>
<b>Technical Documentation</b>	<a href="http://www.roppe.com">www.roppe.com</a>

*\*\*certificate or document available on website*