

<b>Nominal Dimensions</b>	1" (25.4mm) Wide x 18" (45.7 cm) Long x 0.004" Thick
<b>ASTM F152 - Copper Strip</b>	C11000 Electrolytic Tough Pitch
<b>Chemical Properties</b>	Minimum 99.90% Copper
<b>Electrical Conductivity</b>	100.000 % IACS @ 68° F (annealed) 58.108 MS/m @ 68° F (annealed)
<b>Electrical Resistance</b>	0.0172 Ω / M
<b>Density</b>	0.322 pounds / cubic inch @ 68° F (annealed)
<b>Modulus</b>	17000 Elastic Modulus in tension ksi
<b>Acclimation Time</b>	48 Hours
<b>Service &amp; Storage Temperature</b>	65° - 85° F <i>See installation document for full installation details regarding approved substrates, job site conditions and acclimation procedures.</i>
<b>Warranty</b>	Lifetime Electrical Resistance
<b>Approved Adhesives</b>	Excelsior ASD-800, Wet-Set Acrylic ESD Adhesive Excelsior USD-810, Urethane Two-Part ESD Adhesive
<b>Technical Support</b>	<a href="mailto:solutions@rhctechical.com">solutions@rhctechical.com</a>
<b>Product Support</b>	<a href="mailto:support@roppe.com">support@roppe.com</a>
<b>Technical Documentation</b>	<a href="http://www.roppe.com">www.roppe.com</a>