

| | |
|---|---|
| Available Lengths | 72" |
| Finish | 10" Height x 0.080" Thickness 12" Height x 0.080" Thickness |
| ASTM E648 (NFPA 253) - Critical Radiant Flux | Class 1, $\geq 0.45 \text{ W/cm}^2$ |
| ASTM E662 (NFPA 258) - Smoke Density | Passes, ≤ 450 |
| CAN/ULC-S102.2 - Surface Burning | 115 Flame Spread Rating 275 Smoke Developed Classification |
| ASTM F925 - Chemical Resistance | Excellent with chemicals listed in standard, Additional chemicals available via chart |
| ASTM F1514 - Heat Stability | Excellent, $\Delta E \leq 8$ |
| Sustainability Information | Same as Rubber Stair Tread |
| Acclimation Time | 48 Hours |
| Service & Storage Temperature | 65° - 85° F |
| <i>See installation document for full installation details regarding approved substrates, job site conditions and acclimation procedures.</i> | |
| Product Warranty | 5 Years |
| <i>See product warranty for full details regarding limitations and warranty coverage.</i> | |
| Approved Adhesives | Excelsior TP-620, Pressure Sensitive Tread Tape Excelsior AW-510, Wet-Set Acrylic Excelsior C-631, Contact Adhesive |
| Technical Support | solutions@rhctechnical.com |
| Product Support | sales@roppe.com |
| Technical Documentation | www.roppe.com |

