


# RUBBER ACCESSORIES


**ROPPE.**  
Proven. Flooring. Experiences.

## EDGE GUARDS




#34 underlap carpet edge 3/16"

- 3/16" butting gauge; fast taper; long flange
- Minimum Installation Radius: 6 ft.
- 16 9-ft. secs. per ctn. (144 ft.)





#39 glue-down carpet edge 5/16"

- 5/16" butting gauge undercut
- Minimum Installation Radius: 5.5 ft.
- 10 9-ft. secs. per tube (90 ft.)




#35 underlap carpet edge 1/4"

- 1/4" butting gauge
- Minimum Installation Radius: 8 ft.
- 16 9-ft. secs. per ctn. (144 ft.)





#40 carpet edge guard 9/32"

- 9/32" butting gauge undercut; long flange, faster taper than #38
- Minimum Installation Radius: 6 ft.
- 10 9-ft. secs. per tube (90 ft.)





#36 underlap carpet edge 5/16"

- 5/16" butting gauge
- Minimum Installation Radius: 6 ft.
- 16 9-ft. secs. per ctn. (144 ft.)




#41 tackless carpet bar 1/4"

- 1/4" butting gauge to accept tackless strip; deep undercut; long flange
- Minimum Installation Radius: 12 ft.
- 10 9-ft. secs. per tube (90 ft.)




#37 underlap carpet edge 3/8"

- 3/8" butting gauge
- Minimum Installation Radius: 6 ft.
- 16 9-ft. secs. per ctn. (144 ft.)




#42 custom carpet edging 3/16"

- Notched at 1/8"; undercut 3/16"; long, smooth taper (similar to #38 and #39)
- Minimum Installation Radius: 5.5 ft.
- 10 9-ft. secs. per tube (90 ft.)



#38 glue-down carpet edge 1/4"

- 1/4" butting gauge undercut; long flange smooth taper
- Minimum Installation Radius: 5.5 ft.
- 10 9-ft. secs. per tube (90 ft.)



#43 custom carpet edging 1/4"

- Same as #42 above except undercut 1/4"; notched at 1/8"
- Minimum Installation Radius: 5.5 ft.
- 10 9-ft. secs. per tube (90 ft.)